



PowerXtreme



PowerXtreme X60

Battery 12,8V 60Ah

* After registration



LiFePO4: the safest lithium technology

Very low self-discharge, low maintenance & safe



Extreme power

150A continuous - 300A peak



Sustainable

More than 3000 cycles - completely recyclable



Lightweight and small

Only 7,4 kg - 257x179x142 mm



Smart Bluetooth (PowerXtreme PRO App), CI-Bus (LIN-Bus)

Wireless information on your smart device including on/off function



Simple installation

Including pole set, practical mounting bracket and supplied charger



Protected (BMS) overcurrent, overvoltage, short circuit, temperature

www.powerxtreme.eu



PowerXtreme

Technical specifications	
Model	X60
Article number	EM010060
Cell chemistry	LiFePO4 (Lithium Iron Phosphate)
Lifetime	> 3000 cycles (80% DOD)
Warranty	5 years (2 years standard + 3 years extra after registration) and maximum 3000 cycles
Housing	ABS
Connection	M6 internal thread + 2 separate battery poles
IP class	IP 62
Storage temperature	-10°C to +45°C
Communication	Bluetooth via PowerXtreme PRO App + Smart display capability CI-Bus (LIN-Bus)
Usage	Caravan mover / On board-battery
Output (discharge)	
Nominal voltage	12.8V
Capacity	60Ah / 768Wh
Nominal continuous current	150A / 1800W
Short-term current (≤ 30 sec)	200A / 2400W
Peak current (≤ 3 sec)	300A / 3600W
Operating temperature	-20°C to +60°C
Maximum discharge voltage	$\leq 10.5V$
Input (charge)	
Charging voltage	14.4–14.6V
Maximum charging current	55A (via battery terminals)
Charge temperature	0°C to +45°C
Internal charger	14.4V / 6A
AC input charger	200 - 240 VAC
Dimensions	
Length	257 mm
Width	179 mm
Height	142 mm
Weight	7,4 kg
Safety / Certification	
Security	Overcurrent / over- and undervoltage / short circuit / temperature
Compliance	UN38.3 / MSDS / CE / ECE-R10.6

